



Decision Technology
7 St Johns Road
East Molesey
United Kingdom KT8 9JH

Phone +44 (0) 20 8979 5533

Fax +44 (0) 20 8979 7045

www.decisiontechnology.co.uk

DECISION TT LABELS

Front Label

Reference	Semi Gloss
General characteristics	White coated, calendared, woodfree paper.
Grammage (gr/m ²) ISO 536	80
Thickness (µm) ISO 534	65
Gloss 75° (%) TAPPI T480	>64
Dry opacity (%) ISO 2471	88

Adhesive

Reference	Permanent
General characteristics	Permanent acrylic water based adhesive. Good adhesion to a wide variety of substrates, including non-polar surfaces. Specially recommended for products that are deep-frozen after the label application. The adhesive conforms with the Bfr XIV regulations for direct contact with dry and moist non-fatty foodstuffs .
Tack (N) glass FTM-9	>9
Cohesion (h) 1kg FTM-8	>2
Labelling temperature (°C)	>0°C
Usage temperature (°C)	-35°C/+60°C

Support

Reference	Glassine Liner
General description	Supercalendered glassine paper, cream.
Grammage (gr/m ²) ISO 536	60
Thickness (µm) ISO 534	50
Transparency (%) ISO2469	48

Our Decision brand labels are manufactured for us by an organisation with over 30 years experience in label & tag manufacturing.

Our manufacturer is fully ISO accredited, to ISO 9001:2008, and is subject to assessment by an external body.

Our manufacturer has achieved PEFC (Programme for the Endorsement of Forest Certification) and FSC (Forest Stewardship Council®) Certification which enables them to source paper products that can be traced to legal and well-managed forests, reflecting their commitment to acting responsibly within the environment.