



8000T Z-Destruct PE

Permanent labels

Thermal transfer

Description

A destructible white polyethylene that delivers premium thermal transfer print quality on Zebra ZPL mid-range and high-performance printers (not recommended on desktop or mobile printers). 8000T Z-Destruct PE is designed to break apart once applied. This is accomplished by its extremely aggressive adhesive and destructible facestock. This product is not suitable for fanfolding. (For application onto apolar surfaces and plastic surfaces with a low surface energy, it is recommended that this product is supplied with faceslits in the label to retain its full tamper evident qualities). Indoor use only. For outdoor use, please select 8000T Z-Destruct Vinyl as an alternative material.

Suggested Applications

- Warranty labels
- Tamper evident asset tracking labels
- Serialised data labels.
- Applications requiring destructible bar codes

Technical Specifications

	Description	Caliper
Facestock	White destructible polyethylene	50 microns
Adhesive	Permanent rubber based	26 microns
Liner	85gsm Glassine liner	80 microns
		Total 156 microns

Recommended Zebra printers: Mid-range and high-performance thermal printers

Recommended Zebra ribbons: 5095

Minimum application temperature: 10°C

Service temperature range: -40°C to 80°C

Recommended storage conditions: One year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order SAM5448.