



PolyE 3000T Gloss

Permanent labels

Thermal Transfer

Description

A gloss white polyethylene facestock, topcoated for use through Zebra thermal transfer printers. PolyE 3000T Gloss is supplied with an all purpose, permanent acrylic adhesive, to make this an ideal low-cost material for applications where more tear resistance is required than a paper label can give. With a pure polyethylene facestock, it is also environmentally-friendly, making it an ideal label for use on pallet shrinkwrap which must later be recycled.

Suggested Applications

- Labelling of products and packaging
- Pallet labelling suitable for recycling with shrink-wrap
- Cost effective outdoor labelling for plants, garden and DIY products (approx. 9 months)
- Medium-life product and box labelling
- Shelf edge labelling in retail applications
- Work in progress labels

Technical Specifications

	Description	Caliper
Facestock	100gsm gloss white topcoated polyethylene film	100 microns
Adhesive	Acrylic based, permanent adhesive	20 microns
Liner	64gsm Glassine liner	56 microns
	Total	176 microns

Recommended Zebra printers: mid-range and high-performance thermal transfer printers

Recommended Zebra ribbons: 4800, 5095

Minimum application temperature: 5°C

Service temperature range: -10°C to 60°C

Recommended storage conditions: One year duration when stored at approx 20C 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order SAM5730.