

## Z-Ultimate® 3000T White



Available  
from stock  
on ZipShip

<b>Media Type</b>	Label	✓	<b>Film Type</b>	Polyethylene	
	Receipt			Polyolefin	
	Tag			Polypropylene	
	Wristband			Polyester	✓
<b>Material Type</b>	Paper			Polyimide	
	Synthetic	✓		<b>Properties</b>	Cold Temperature
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)		Deep Freeze		✓
	Thermal Transfer (Ribbon Required)	✓	High Temperature		✓
<b>Adhesive Type</b>	Permanent	✓	Ultra High Temperature		
	Removable		High Tack		
	No Adhesive		Chemical Resistance		<b>Harsh</b>
<b>Finish</b>	Matte		<b>Environment</b>	Indoor	✓
	Gloss	✓		Outdoor	✓

### Additional Features

- Outstanding print quality, smear and scratch resistance
- Good resistance to moderate and harsh chemicals and solvents
- Excellent adhesion to a wide range of surfaces
- Tear and water resistant
- UL approved for electronic equipment, as a label which will last as long as the product
- CSA certified for use with Zebra 4800, 5095, 5100 ribbons
- BPA free
- Latex free adhesive

### Suggested Applications

- Sterile services labelling including autoclave
- Capital asset labelling and tracking
- Rating plate and component labelling
- Shelf or scan-pallet labels
- Water-immersed labels or labels which are continually scanned
- Applications where labels are in contact with moving parts or friction conveyor drives
- Labels exposed to acid or alkali solutions; top side printed circuit board applications
- Gloss materials are not suitable for fanfold applications

### UL Recognised and CSA Certified

UL and CSA approved for use with the following ribbons:

- 4800
- 5095
- 5100



### Technical Specifications

	Description	Caliper
<b>Facestock</b>	Gloss white topcoated polyester	50 microns
<b>Adhesive</b>	Permanent acrylic adhesive	22 microns
<b>Liner</b>	65gsm white glassine liner	56 microns
	<b>Total</b>	<b>128 microns ±10%</b>

**Recommended Zebra Printers:**

P4T, desktop, mid-range and high-performance thermal printers

**Recommended Zebra Ribbons:**

4800, 5095, 5100

**Minimum Application Temperature:**

When the label is applied, the environment and surface should be above this temperature

2°C

**Service Temperature Range:**

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-40°C to 150°C

**Recommended Storage Conditions:**

Storage of product before use

1 year duration when stored at 21°C at 50% RH

**Expected Life Span in Application:**

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, 1 year+  
Outdoor use, 1 year+

### Suggested Ribbons for Applications requiring Chemical Resistance

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
5095	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓					
5100	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓					

“✓” indicates acceptable chemical resistance

4800 ribbon will also provide chemical resistance, however requires testing in application

### 180° Angle Peel Adhesion at Room Temperature (N/m):

Steel		Polycarbonate		Polyethylene	
5 min	24 hr	5 min	24 hr	5 min	24 hr
561	671	407	517	44	66

### Facestock Tensile Strength

- Machine direction: 18,000 psi
- Transverse direction: 22,000 psi

Note: For guidance only, not to be used for setting specifications

### Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order from the ZipShip price list or order sample roll SAMPLE5164 or SAMPLE5164-D for desktop printers.