



General Purpose Corded Handheld Area Imager Bar Code Reader for Electrostatic Discharge Control

With rich feature sets and extensive model options, the Gryphon product series from Datalogic Scanning represents the premium level of data collection equipment for general purpose applications. The Gryphon D432 Plus ESD reader has been specially developed by Datalogic Scanning to satisfy the strict requirements for EPA (ESD Protected Area) use.

ESD is a phenomenon that occurs when an object has an imbalance in its electrical charge: a fast charge transfer between objects with differing electrostatic potential caused by contact or by the proximity of the two objects. Wherever electronic components are handled, installed or assembled, ESD poses a threat to product quality. With technological advances in electronics an increasing number of these components are susceptible to damage or destruction by increasingly lower voltage levels. ESD events can also compromise the measurements taken by very sensitive instruments, like those used in hospital and medical analysis laboratories.

The most advanced polymer and elastomeric

technologies are used for the ESD-safe Gryphon D432 Plus reader. The body of the product is composed of a slightly conductive plastic, rather than an insulating one, preventing the accumulation of tribocharges. Specific cables additionally guarantee ESD safety between any two points.

These specialized protective features are added to the same outstanding reading snappiness and full 2D decoding capability of Gryphon D432 Plus. Enhanced optics with improved 'motion tolerance' allows codes placed on fast moving objects to be easily and quickly captured, creating the ideal reader for tasks requiring high throughput like those found in light industrial manufacturing environments.

The Gryphon D432 Plus ESD features Datalogic's exclusive patented 'Green Spot' providing good read feedback directly on the code which is especially useful for noisy environments. Aiming at the image to be captured is easy and intuitive, with the single click trigger that enables the Datalogic 5-dot aimer, marking the four corners and center of the reading area.



Features

- Certified between static dissipative ($10^6 \Omega$ and $10^{12} \Omega$) and conductive ($10^3 \Omega$ and $10^6 \Omega$) range
- Omnidirectional reading
- Advanced 'motion tolerance' optics
- Supports 1D, 2D and postal codes plus stacked and composite codes like PDF417 and GS1 DataBar™
- Datalogic's patented 'Green Spot' for good-read feedback and instinctive 5-dot aimer



Specifications

DECODING CAPABILITY

1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes

2D CODES

Aztec Code; Data Matrix; MaxiCode; QR Code

POSTAL CODES

Australian Post; China Post; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)

STACKED CODES

EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

ELECTRICAL

CURRENT

Operating (Typical): 245 mA @ 5 VDC
Standby/Idle (Typical): 120 mA @ 5 VDC

INPUT VOLTAGE

4.75 - 5.25 VDC

ENVIRONMENTAL

AMBIENT LIGHT

0 - 100,000 lux

DROP RESISTANCE

Withstands repeated drops from 1.2 m / 3.9 ft onto a concrete surface

ESD FEATURES

Certification Rank: Certified between static dissipative ($10^6 \Omega$ and $10^{12} \Omega$) and conductive ($10^3 \Omega$ and $10^6 \Omega$) range
Residual Voltage: < 5 V

ESD PROTECTION (AIR DISCHARGE)

8 kV

HUMIDITY (NON-CONDENSING)

0 - 95%

PARTICULATE AND WATER SEALING

IP30

TEMPERATURE

Operating: 0 to 50 °C / 32 to 122 °F
Storage/Transport: -20 to 70 °C / -4 to 158 °F

INTERFACES

Keyboard Wedge; RS-232; USB

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE

Black

DIMENSIONS

17.9 x 8.1 x 9.8 cm / 7.0 x 3.2 x 3.9 in

WEIGHT

198.0 g / 7.0 oz

READING PERFORMANCE

IMAGE CAPTURE

Wide VGA: 752 x 480 pixels
Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2

IMAGER SENSOR

2D CMOS Array: 752 x 480 pixels

LIGHT SOURCE

Aiming: 630 - 670 nm VLD

PRINT CONTRAST RATIO (MINIMUM)

23%

READING ANGLE

Pitch: 35°; Roll (Tilt): +/- 360°; Skew (Yaw): +/- 40°

READING INDICATORS

Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback; Good Read LED

RESOLUTION (MAXIMUM)

Data Matrix: 0.168 mm / 6.6 mils; Linear: 0.100 mm / 4.0 mils

READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.
10 mils Data Matrix: 1.5 to 14.0 cm / 0.6 to 5.5 in
10 mil PDF: 0.5 to 22.0 cm / 0.2 to 8.6 in
EAN13 - 13 mils: 1.5 to 22.0 cm / 0.6 to 8.6 in

SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

The Quick Reference Guide for this product can be referred to for a complete list of certifications.

ENVIRONMENTAL COMPLIANCE

Complies to China RoHS; Complies to EU RoHS

LASER CLASSIFICATION

Caution Laser Radiation - Do not stare into beam; CDRH Class II; IEC 60825 Class 2

LED CLASSIFICATION

IEC 60825 Class 1 LED

UTILITIES

DATALOGIC ALADDIN™

Datalogic Aladdin configuration program is available for download at no charge

WARRANTY

5-Year Factory Warranty



Mounts/Stands

- 90ACC1760 Hands Free Stand (STD-GRYPHON) for Gryphon Dx000/D110/Mx00, DLC707x-M1
- 90ACC1770 Desk/Wall Holder (SPC-GRYPHON)
- 90ACC1873 Hands Free Stand (STD-1010) for Gryphon Dx20/BTx00
- 90ACC1876 PLATE, Metal Plate for STD-Gryphon, STD-10xx

© 2009-2010 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo and Gryphon are trademarks of Datalogic S.p.A.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-GRYPHOND432ESD-ENA4 20100625

www.scanning.datalogic.com