

3200

Handheld Linear Imager

The 3200 delivers quality linear barcode scanning and user friendly ergonomics, combined in a solution that's affordable and dependable for a wide variety of applications. Whether you're automating a pen and paper process, or require a high-quality yet cost effective barcode scanner to replace your existing devices, the 3200 is an ideal solution.

Linear imaging technology provides high scanning performance on all linear barcodes – even those that are damaged or poorly printed - and features the added value of being 100% solid-state, with no moving parts that can fail or become misaligned.

Unlike other value-priced solutions that sacrifice usability features, the 3200 provides an ergonomic pistol-grip and user-preferred finger trigger design for comfortable and intuitive use.

With a 2-year warranty and durable design, the 3200 provides a great value to customers who require reliable barcode scanning solution at an affordable price.



Features

- **Linear Imaging Technology:** Fast barcode scanning, even on poorly printed or damaged linear codes.
- **User-Friendly Design:** Pistol-style with index finger trigger ensuring operator comfort and ease of use.
- **Reliable:** The durability of 100% solid state technology and a 2-year warranty.
- **Ease of Connectivity:** Common interfaces are integrated to ensure fast and easy connection to your host or PC.
- **Future Proof Symbology Support:** GTIN compliant, GS1 DataBar capable.
- **Intuitive Aiming Line:** Thin, crisp aiming line for ease-of-use in scanning bar coded menus and densely populated documents.
- **Intuitive User Feedback:** Fully programmable options for application-specific "good read" LED and beeper settings.

High Performance Linear Image Scanners:



3200 Specifications

Performance			
Illumination:	630 NM Visible Red LED		
Receiving Device:	2048 element linear imager		
Reading Distance:	From .5 in. (1.3 cm) to 10 in. (25 cm) on medium density bar codes		
Reading Width:	15 mil code 4 in. (11 cm) wide at 3.5 in. (9 cm)		
Resolution:	4 mil. at 4 in. (10 cm) distance		
Skew Angle:	±55°		
Pitch Angle:	±55°		
Minimum Symbol Contrast:	30%		
Scan Rate:	200 plus scans per second		
Mechanical/Electrical			
Length:	3.7 in. (9.5 cm)		
Height:	6.0 in. (15.2 cm)		
Width:	2.7 in. (6.8 cm)		
Weight:	5.1 oz. (143 g)		
Housing:	UL 94V0 grade		
Power Requirements:	3200: 4.75 - 5.25Vdc at scanner		
Current Draw (Maximum):	Input 5 V	Scanning 235mA	Idle 86mA
Power Supply			
Noise Rejection:	Maximum 100mV peak to peak, 10 to 100 kHz		
Environmental			
Operating Temperature:	+32°F to +122°F (0°C to +50°C)		
Storage Temperature:	-4°F to 140°F (-20°C to +60°C)		
Humidity:	0 to 95%, non-condensing		
Mechanical Shock:	Operational after 25 drops from 4 ft. (1.2 m) to concrete		
Ambient Illumination:	0 - 70,000 lux		
ESD Protection:	Exceeds CE EN55024		
Vibration:	Withstands 5G peak from 22 to 300 Hz		
Agency:	USA: FCC Part 15 subpart B Class B. Canada: ICES-003 Class B. Europe: CE 2004/108/EC EMC Directive to EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3. 2006/95/EC Low Voltage Directive Australia/NZ: C-Tick mark Japan: VCCI		
MTBF:	per MIL-HDBK-217F Ground Benign exceeds 85,000 hours		
Symbolologies:	Codabar, Code 3 of 9 including PARAF, Interleaved 2 of 5, Straight 2 of 5 Industrial, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Postal Code, GS1 DataBar. 2005 Sunrise/GTIN compliant		
Interfaces:	3200: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, USB, and (Host Powered) TTL level RS-232		
Warranty:	Two year factory warranty.		

Typical Performance*	
Narrow Width	Depth of Field
5.0 mil	1.5 - 4.5 in. (3.8 - 11.4 cm)
13 mil (100% UPC)	.5 - 9 in. (1.3 - 23 cm)
*may be impacted by bar code quality and environmental conditions	

Automation and Control Solutions
Honeywell
Imaging and Mobility
700 Visions Drive
PO Box 208
Skaneateles Falls, NY 13153-0208
www.honeywell.com/aidc

