



**Decision Technology**  
**7 St Johns Road**  
**East Molesey**  
**United Kingdom KT8 9JH**

**Phone +44 (0) 20 8979 5533**

**Fax +44 (0) 20 8979 7045**

**[www.decisiontechnology.co.uk](http://www.decisiontechnology.co.uk)**

## **DECISION DT-TOP LABELS**

### **Material Specification**

#### **Face/Label Material**

General characteristics	High sensitivity direct top coated paper with back protection.
Grammage (gr/m <sup>2</sup> )	75
Caliper (µm)	72
Dry opacity (%)	85

#### **Adhesive**

General characteristics	Permanent acrylic water based adhesive. Good adhesion to a wide variety of substrates, including non-polar surfaces. The adhesive has ISEGA approval and can be used for direct contact with dry and moist non-fatty foodstuffs.
Labelling temperature (°C)	>5°C
Usage temperature (°C)	-35°C to 60°C

#### **Liner**

General description	Supercalendered glassine paper
Grammage (gr/m <sup>2</sup> )	57

Our Decision brand labels are manufactured for us by an organisation with over 30 years experience in label & tag manufacturing.

Our manufacturer is fully ISO accredited, to ISO 9001:2008, and is subject to assessment by an external body.

Our manufacturer has achieved PEFC (Programme for the Endorsement of Forest Certification) and FSC (Forest Stewardship Council®) Certification which enables them to source paper products that can be traced to legal and well-managed forests, reflecting their commitment to acting responsibly within the environment.