



Phone +44 (0) 20 8979 5533

Fax +44 (0) 20 8979 7045

Decision Technology
7 St Johns Road
East Molesey
United Kingdom KT8 9JH

www.decisiontechnology.co.uk

DECISION DT LABELS

Material Specification

Face/Label Material

General characteristics	High sensitivity thermal economy paper
Grammage (gr/m2)	75
Thickness (µm)	81
Dry opacity (%)	90

Adhesive

General characteristics	Permanent acrylic water based adhesive. Good adhesion to a wide variety of substrates, including non-polar surfaces. The adhesive has ISEGA approval and can be used for direct contact with dry and moist non-fatty foodstuffs.
-------------------------	--

Labelling temperature (°C)	>5°C
Usage temperature (°C)	-35°C to 60°C

Liner

General description	Supercalendered glassine paper
Grammage (gr/m2) ISO 536	60

Our Decision brand labels are manufactured for us by an organisation with over 30 years experience in label & tag manufacturing.

Our manufacturer is fully ISO accredited, to ISO 9001:2008, and is subject to assessment by an external body.

Our manufacturer has achieved PEFC (Programme for the Endorsement of Forest Certification) and FSC (Forest Stewardship Council®) Certification which enables them to source paper products that can be traced to legal and well-managed forests, reflecting their commitment to acting responsibly within the environment.