ZEBRA CAPTURE YOUR EDGE

ZeroLiner 1000D

ZeroLiner direct thermal labels

A direct thermal paper label with a permanent rubber adhesive and a gloss finish suitable for use indoors, our ZeroLiner 1000D is our entry-grade liner-free option designed for use in standard shipping and logistics applications. Ideal for use in our desktop printers which require low-medium print volumes. This has good smear and scratch resistance due to the siliconized topcoat of the face of the material.



ZeroLiner Benefits

There is a unique combination of benefits where the absence of a liner allows for more labels per roll and no waste having both environmental and safety implications in applications. There is an immediate waste reduction via reduced roll volume which takes less space, less manpower and a huge saving on liner take up equipment as this is no longer required. There would also be an increase in productivity as fewer roll changes would be needed in the printer or on press.

The manufacturing journey of ZeroLiner label is significantly shorter than that of linered labels, resulting in overall CO2 savings through less transport and manufacturing. As label liner is difficult to recycle, the waste usually ends up in landfill, being burnt for fuel or being stored in large volumes before being collected for recycling, which can lead to cluttered work areas and sometimes accidents. With ZeroLiner the above does not apply. Once you have applied your labels you're finished.

Simplified Printing - No Ribbon Required

The ZeroLiner 1000D is compatible with Zebra direct thermal, desktop printers, providing all the benefits of direct thermal printing -there's no ribbon to stock, monitor and replenish.

ZeroLiner Printers

Zebra's Linerless capable printers feature specially designed platen rollers and cutters. Zebra's ZeroLiner labels are created to give the best performance by printer type.

- Desktop printers use linerless label rolls that feature a "clean-cut" adhesive, optimized for use with a cutter.
- Mobile printers need to release easily from the roll, to enable consistent feed so as not to stress the motor in the printer AND needs to release easily from the platen while adhering well in the application.

All Zebra ZeroLiner label rolls are pre-tested to ensure best performance.

ZeroLiner 1000D Specifications

Material Construction	
Facestock	Smooth white silicone topcoated paper; -8mils
Adhesive	Permanent rubber adhesive
Liner	N/A
Total thickness +/-10%	98mils
Environment	Indoor use
Temperature Perfor	mance
Minimum Application Temperature ¹	47 °F/8 °C
Service Temperature Range ²	14 °F to 158 °F/-10 °C to 70 °C
Recommended Printers and Settings	
Printers	Direct Thermal Printer; Zebra linerless desktop printers
Ribbons	N/A
Regulatory and Con	ipliance
REACH, RoHS, EN71-3 Safe BPA and BPS Free	ety of Toys and the UK Packaging Regulations 1998,
Product Performance	e and Sustainability
Recommended Storage Conditions ³	1 yr duration when stored at 22 °C at 50% RH Rolls must be sored below 35 °C Relative humidity must be less than 85% Rolls must be stored indoors and away from direct sunlight Rolls must be kept in their original packaging
Expected Life Span in Application ⁴	Indoor use, 1 to 2 yrs
Footnotes	

- 1. When the label is applied, the environment and surface should be above this temperature.
- $2. \ Following \ correct application \ and \ appropriate \ dwell time (usually 24hrs) the$ $media\ will\ with stand\ this\ temperature\ range.$
- 3. Storage of product before use.
- 4. Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated.

Markets and **Applications**

Manufacturing

• Work in progress labeling

Retail

• Product and price labelling

Government

· Postal applications

Other

• Applications that do not allow the use of a